Type CBCN
Belt Drive Propeller Fan

P.O. Box 2300 Jacksonville, Florida 32203
Phone: (904) 389-3646
Fax: (904) 387-3449 • (904) 381-7560
E-mail: info@coolair.com
Website: americancoolair.com

Abbreviations for Accessories

S – Type S automatic wall shutter
SE – Type S motorized wall shutter (specify voltage)
SGF – Front safety guard
SGM – Motorside safety guard
MH – Metal housing
MHG – Metal housing guard
EPX – 6 mil epoxy finish
HDG – Hot dip galvanizing
IH – Intake hood
DH – Discharge hood

Standard Fan Features

- Welded steel construction
- Rugged angle frame
- Heavy duty pillow block ball bearings
- Three or six adjustable pitch cast aluminum airfoil blades
- Variable pitch pulleys (most models)
- Shipped completely assembled
- UL Listed for Standard 705 (most models)

Dimensions

Dimension A is the O.D. of the square fan panel.

Dimension B is the depth from the face of the fan panel to the back of the fan frame.

Dimension C is the maximum with constant speed, 3-phase TEFC motor of maximum horsepower for fan size and style indicated. This dimension will vary with the type and HP of the motor actually selected.

Dimension G is the diameter of the installation holes.

Drawings of belt, drive, and blade assembly are schematic. Multiple belts are used on certain sizes and HPs.



Fan Size	Dimensions in Inches						
	A	B	C	D	E	F	G
48	56	6 5/8	21	8	6	1	3/8
54	62	6 5/8	21	8	6	15/16	3/8
60	68	6 5/8	21	11	9	1	1/2

Specifications

		FAN DATA					MOTOR DATA						
FAN NO.	QTY.	MODEL NO.	CFM	SP	RPM	SONES	HP	RPM	VOLTAGE	PH	HZ	ENCLOSURE	ACCESSORIES AND REMARKS

PROJECT _____ ENGINEER _____ SUBMITTED BY _____ DATE _____

LOCATION _____ CONTRACTOR _____ APPROVED BY _____ DATE _____

Form No. 223-50-1 (9-19) Printed in U.S.A. © by American Coolair Corporation 2019